

The 130/131 contact thermometers offer fast response and laboratory accuracy. These thermometers offer 0.1°C/0.1°F resolution over the entire measurement ranges. A rugged holster protects both models.

- Easy to use: Remove the protective sheath, press the ON/OFF button and insert into the testing area.
- LCD screen shows readings in Fahrenheit or Celsius
- Range: -40° to +250° C/ -40° to +482° F
- 132 is pen type humidity & temperature meter

High Accuracy

Faster Reaction time 6s (133A)



EMC  
EN: 61326  
EN: 60825-1



Model 133A

Features						
	130	130A	131/133	131A	132	133A
User Selectable °C or °F	*	*	*	*	*	*
Resolution 0.1°C/0.1°F	*	*	*	*	*	*
Sampling time 2.0 seconds	*	0.5S	*	0.5S	*	0.5s
Reaction time	10s	6s	10s	6s	10s	6s
LCD display	*	*	*	*	*	*
Max / Min Hold and Data Hold			*		*	*
Auto Power Off	*	*	*	*	*	*
Humidity & Temperature measurement	Temp.	Temp.	Temp.	Temp.	*	Temp.
2.0mm Diameter probe shaft tip		*		*		*



Specifications								
Function	Range	Basic Accuracy	130A	131A	133A	130	131/133	132
Temperature	-40~250°C/482°F	±1.5%				*	*	*
	-40~200°C/392°F	±1.0%	*	*	*			
Humidity	10%RH~95%RH	±3.5%						*

**Size(HxWxD):** 130:150mm x 40mm x 28mm  
131/132/133:211mm x 32mm x 19mm

**Weight:** 130:19g  
131/132/133:35g

**Accessories :**  
One LR44(1.5V) button battery and clamshell.



Model 132

Model 130



Model 133

Model 131