

- 7 functions Pen-type Digital Multimeters
- Large 3-3/4 digital LCD display with Bargraph
- Full function indication
- Diode and audible continuity

Model 3280B



Specifications								
Function	Max range	Basic accuracy	3216	3218	3219	3280	3280B	3290
Voltage DC	600V	±0.8%	*	*	*	*	*	*
Voltage AC	600V	±1.2%	*	*	*	*	*	*
Current DC		±1.5%		340mA	400mA	200mA		400mA
Current AC		±2.0%		340mA	400mA	200mA		400mA
Resistance		±3.0%	20MΩ	30MΩ	40MΩ	20MΩ	20MΩ	40MΩ
Non-contact voltage: 50-600V						*	*	*
Continuity: <35Ω								
Diode test: Test voltage max. 3.4V								

Size(HxWxD): 220mm x 40mm x 33mm

Weight: 215g

Accessories:

Clamshell and button battery

Model 3218



EMC & LVD

EN: 61326

EN: 61010-1

EN: 61010-02-032

EN: 61010-02-033



DT-3260 Smart Pen-type Digital Multimeter

3260 is ideal for electrical trouble shooting, which can check components (resistance, capacitance, diode and continuity) and circuit fault.

All inputs are protected to EN 610101-1 CATIII 600V.

Features

- Automatic DCV or ACV selection, Capacitance, Resistance, Continuity and diode selection
- 6000 counts LCD display
- Auto/manual ranging
- Data Hold/MAX/MIN recording mode
- Auto Power Off
- Wide capacitance range
- Diode Check & Continuity Test

Specifications

Function	Max. Range	Basic Accuracy
Voltage DC	600V	±0.5%
Voltage AC	600V	±1.0%
Current DC	400mA	±1.0%
Current AC	400mA	±1.5%
Resistance	40MΩ	±1.0%
Capacitance	40mF	±3.5%



EMC & LVD

EN: 61326

EN: 61010-1

EN: 61010-02-032

EN: 61010-02-033



Safety Conformance

- EN61010-1 CAT III 600V
- Full ranges protection



Model 3260

Size(HxWxD): 230mm x 35mm x 20mm

Weight: 200g

Accessories:

Clamshell and button battery